



Part No:4105/3110/3111/6150/7110 Revision Date: 17th January 2006

This Safety Data Sheet has been prepared in accordance with the requirements of EC Directive 1999/45/EC and provides information relating to the safe handling and use of the product.

QTEK ADHESIVE REMOVER

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION **SECTION 1:**

Product Name: Adhesive Remover

Manufacturer: QTEK Manufacturing Ltd.,

IDA Business Park,

Athenry, Galway, Ireland.

Telephone Number: (353) 91 850222 Fax Number: (353) 91 850233

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Components CAS Number EC Number Risk Hazard Approx. Content

Naphtha (Petroleum), Hydrotreated heavy 64742-94-5 265-150-3 Xn:Harmful R22 >45-65%

Remainder Not Classified

SECTION 3: HAZARDS IDENTIFICATION

Critical Hazards: Harmful, slightly irritating to eyes, skin and respiratory tract

Critical Hazards to man & environment:

Inhalation: Yes Skin Contact: Yes Skin Absorption: Yes Ingestion: Yes Adverse human health effects & symptoms: Moderately irritating to the eyes. May cause corneal surgery. Slightly irritating to the skin. High vapour concentrations are irritating to the eyes and respiratory

tract, may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause to

severe pulmonary injury. Minimal toxicity.

SECTION 4: FIRST AID MEASURES

Eye contact: Immediately flush with water for 15 minutes while lifting eyelids and rolling eyes. Get immediate medical

attention.

Skin contact: Wash promptly with soap and water. May dry out skin. Get medical attention if irritation occurs. Remove

contaminated

Inhalation: Remove person to fresh air. If necessary, restore and support breathing. If breathing is difficult, give

oxygen. Get immediate medical attention.

DO NOT induce vomiting. Get immediate medical attention. If conscious and medical help is not readily Ingestion:

available, give 1 to 2 glasses of water and keep at rest. Never attempt to give anything by mouth to an

unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: (TCC) 45.5°C

> (OCC) 53.3°C

Flammable limits in air: None established for product as a whole.



MATERIAL SAFETY DATA SHEET

Part No:4105/3110/3111/6150/7110 Revision Date:17th January 2006

This Safety Data Sheet has been prepared in accordance with the requirements of EC Directive 1999/45/EC and provides information relating to the safe handling and use of the product.

General Hazard: Flammable liquid.

Can form combustible mixtures at temperatures at or above the flash point. Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/ or vapour) and can be dangerous.

Suitable extinguishing media: Alcohol foam, carbon dioxide, dry chemical, water spray for dilution to

non-flammable mixture.

Decomposition products under

fire conditions:

Combustion produces unidentified organics, oxides of carbon, carbon

dioxide, and carbon monoxide.

Unusual fire and explosion hazards: This liquid is volatile and gives off invisible vapours. Either the liquid

or vapour may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Protective equipment for fire-fighters: Firefighters should have eye protection and wear self-contained

breathing apparatus and protective clothing. Use water spray to cool fire-exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Avoid spraying water directly into storage containers due to

danger of boil over.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Material Release/Spill: Land Spill: Eliminate sources of ignition. Prevent additional discharge of material, if possible to

do so without hazard. For small spills, implement clean-up procedures; for large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, watercourses or low areas. Contain spilled liquid with sand

or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent. Consult an expert on disposal of recovered material and ensure conformity to local disposal

regulations.

Water Spill: Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SECTION 7: HANDLING AND STORAGE

Handling and storage: Store in cool (15-25°C), dry, well ventilated location, out of direct sunlight,

away from incompatible materials. Do not store in open, unlabeled or mislabelled containers. Separate from oxidising agents. Keep containers tightly closed. Avoid contact with skin, eyes and clothing. Avoid breathing mists and vapours. Avoid prolonged and repeated exposure. Use appropriate personal protective equipment. Do not wear contact lenses when working with this

material. No smoking, eating or drinking in handling areas.

Electrostatic accumulation hazard: Material will accumulate static charges, which may cause an electrical spark

(ignition source). Use proper grounding procedures.

General hazard: Can form combustible mixtures at temperatures at or above the flash point.

Static discharge, material can accumulate static charges, which can cause an incendiary electrical discharge. "Empty" containers retain product residue

(liquid and/or vapour) and can be dangerous.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION





Part No:4105/3110/3111/6150/7110 Revision Date:17th January 2006

This Safety Data Sheet has been prepared in accordance with the requirements of EC Directive 1999/45/EC and provides information relating to the safe handling and use of the product.

Personal Protection:

Under normal ventilated use conditions, personal respiratory protection is not typically required. If misting or vapours occur, use NIOSH approved vapour air purifying respirator. Use impervious chemical gloves. Long sleeves, aprons or other protective clothing is suggested to avoid skin exposure. Use chemical safety goggles, face shield, or safety glasses for eye protection. Do not wear contact lenses when working with this material. Have an eye wash and safety shower readily

available.

Workplace exposure guidelines: Avoid direct contact with this material. The use of

mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated. Do not eat, drink or

smoke when working with this material.

Personal protection information given is based upon the general information as to normal use and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other

qualified professional be sought.

None established for product as a whole.

Naphtha (petroleum), Hydrotreated heavy: OSHA PEL: None

established, ACGIH TLV: None established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid Odour: Mild/ Low.

Exposure guidelines for individual components:

Boiling point: 148-152 degrees Celsius.

Solubility in Water: Partial

Exposure guidelines:

Specific Gravity: 0.80 – 0.82 (at 15.5°C) Vapour pressure: Not determined

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat, sparks, flame or other sources of ignition.

Incompatible Materials: Strong oxidising agents

Hazardous polymerisation: Will not occur

Hazardous decomposition products: Oxides of carbon including carbon dioxide and carbon monoxide.

SECTION 11: TOXICOLOGICAL INFORMATION

No information exists for product as a whole

SECTION 12: ECOLOGICAL INFORMATION

Mobility: This product will partially dissolve in water.

Degradability: This product is biodegradable in low concentrations.

Ecotoxicity: Poses a significant risk of oxygen depletion in aquatic systems.

SECTION 13: DISPOSAL CONSIDERATIONS

Page 3 of 3



MATERIAL SAFETY DATA SHEET

Part No:4105/3110/3111/6150/7110 Revision Date:17th January 2006

This Safety Data Sheet has been prepared in accordance with the requirements of EC Directive 1999/45/EC and provides information relating to the safe handling and use of the product.

Disposal of material: Waste must be disposed of in accordance with government environmental control regulations.

Empty containers must be handled with care due to product residue. This material is not a US

EPA hazardous waste.

SECTION 14: TRANSPORT INFORMATION

UN number: NA 1993

US DOT Shipping Name: Compounds, cleaning liquid

US DOT Hazard Class: 3

Harmonised code: 3402.90.5030, Cleaning Preparations

Packing Group: III

US D.O.T. Label: Combustible

SECTION 15: REGULATORY INFORMATION

Label information: Harmful

Risk phrases: R10 Flammable

R22 Harmful if swallowed R36 Irritating to eyes

Safety phrases: S2 Keep out of the reach of children

S7 Keep container tightly closed S23 Do not breathe mist or vapours S24 Avoid contact with the skin

S45 In case of accident or if you feel unwell, seek medical advice immediately

S53 Avoid exposure – obtain special instruction before use

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show container

or label

EC Annex 1 Classification: Xn

Regulations/ references: Refer to the requirements of all relevant local regulations.

SECTION 16: OTHER INFORMATION

NFPA Rating: H=1, F=2, R=0.
Effective Date: 8 October 1999
Supersedes Date: 14 June 1999
Sections Revised: 2, 3, 15

The data contained herein is based on information currently available to QTEK Manufacturing Ltd. and is believed to be factual. As a blender, and compounder, QTEK Manufacturing Ltd. does not manufacture the raw materials used in this product and correspondingly relies on information provided to QTEK Manufacturing Ltd. from material safety data sheets on the specific raw materials in the construction of this material safety data sheet. Such information is, to the best of QTEK Manufacturing Ltd.'s knowledge and belief, accurate and reliable as of the date of this MSDS. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY, OR COMPLETENESS. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular application. This information is not intended to be all-inclusive as of the manner and conditions of use, handling and storage. Other factors may involve other or additional safety or performance considerations. This data is not to be taken as a warranty or representation of which QTEK Manufacturing Ltd. assumes legal responsibility.